

Notes:

The stone paving will be 50mm thick and will be placed on a shallow (75mm max) sub-base of type 1 mot hogging. These will be close jointed to minimise the need for a mortar joint.

Set within the outer row of paving shall be 57 round smooth pebbles of an approximate size of 100mm diameter. These will be set into holes which will be drilled into the paving and fixed into place with mortar.

The stone paving shall be Natural Cut English Riven York Stone with sawn sides

The band details shown shall also be of Riven York Stone

The teardrop sculpture shall be mounted on a stone plinth of 100mm thickness which is to be set over the paving. There will be a concrete foundation to the thickness of 300mm under the area of the stone plinth. There shall be a 12mm thick plate set under the paving to which an anchor rod is attached. This is held into the concrete foundation with 20mm studding bolts. The stone plinth shall have a hole drilled out the middle for the anchor rod to go through. This rod then attaches to the Teardrop Sculpture.

The stone information plinth shall be mounted on a shallow concrete footing onto which there will be studding bolts or similar which can be anchored into the concrete footing to receive the plinth.



Forest Heath • St Edmundsbury
West Suffolk
 working together

West Suffolk, working together
 Forest Heath District Council • St Edmundsbury Borough Council
www.westsuffolk.gov.uk

SITE: Abbey Gardens
 Peace Garden

TITLE: Hard Landscaping Detail

SCALE AT A3: 1:100	DATE: Oct 14	DRAWN: R Davis	CHECKED:
PROJECT NO:	DRAWING NO: 1001	REVISION: 1	